

**Model#: BLC-260X**  
**Exview True Day/Night Camera**



Technical Specification		
<b>Signal System</b>	NTSC	PAL
<b>Imaging Area</b>	4.9mm x 3.7mm	
<b>Image Pickup Device</b>	1/3" type Exview CCD	
<b>Effective Pixels (HxV)</b>	768 x 494	752 x 582
<b>Scanning System</b>	Internal/linelock	
<b>Sync System</b>	2:1 Interlace V: 59.94Hz, H: 15.734KHz	2:1 Interlace V: 50Hz, H: 15.625KHz
<b>Horizontal Resolution</b>	480TVL	
<b>Lens Mount</b>	CS	
<b>Gamma Correction</b>	0.45	
<b>Minimum Illumination</b>	Day mode: 0.04 lux(F1.4, AGC on, 10 IRE) Night mode: 0.005 lux(F1.4, AGC on, 10 IRE)	
<b>S/N Ratio</b>	More than 50dB (AGC off)	
<b>Iris Control</b>	Video/DC Driver	
<b>Gain Control</b>	Auto(Standard/Wide)	
<b>White Balance</b>	ATW1/ATW2	
<b>Electric Shutter</b>	Auto 1/60 to 1/100,000sec. / manual 8 steps (1/60, 1/100, 1/250, 1/500, 1/1K, 1/2K, 1/4K, 1/10Ksec.)	Auto 1/50 to 1/100,000sec. / manual 8 steps (1/50, 1/120, 1/250, 1/500, 1/1K, 1/2K, 1/4K, 1/10Ksec.)
<b>BLC</b>	On/Off	
<b>Day/Night Mode</b>	Auto/Manual	
<b>Video Output</b>	1Vpp composite output, 75 ohm	
<b>Power Requirement</b>	DC12V / AC24V AC90~260V	
<b>Power Consumption</b>	10W (max.)	
<b>Operating Temperature</b>	-10 °C~ 50 °C	
<b>Operating humidity</b>	30% ~ 90% RH	
<b>Storage temperature</b>	-20 °C~ 60 °C	
<b>Dimensions (WxHxD)</b>	50mm x 62mm x 126mm (1.96" x 2.44" x 4.96")	
<b>Weight</b>	500g approx.	