

STANDALONE NETWORK DVR – ADR-800 SERIES

ADR-800 SERIES MULTIPLEX DVR WITH NETWORKING



:: MAIN FEATURES ::

- JPEG2000 Algorithm compression
- Triplex(playback/recording/ethernet)
- Multi Language OSD
- IR Remote Controller
- Jog-Shuttle for convenience search
- USB port for firmware upgrade
- VGA option available(support TFT LCD monitors)
- Support DDNS, CMS (central monitoring system)

SPECIFICATION			
MODEL	ADR-804	ADR-808	ADR-816
COMPRESSION	JPEG2000 Algorithm		
STORAGE CAPACITY	2HDDs, Up to 500G per each HDD		
VGA	1CH (Supports TFT LCD MONITOR)		
VIDEO INPUT	4CH	8CH	16CH
VIDEO OUTPUT	Monitor/VCR		
AUDIO (Option)	Input: 4CH audio input, Output: 1CH audio output		
SPLIT SCREEN	1/4/6/8/9 Split Screen		
COMPRESSED RATING	Low, Mid, High, Super, Hyper		
RECORDING SPEED	120fps(full), 240fps(dual),480fps(quad)		
RECORDING RESOLUTION	Full(720x240/720x288), Dual(360x240/360x288), Quad(360x120/360x144)		
DISPLAY	Real Time for all channel		
SIMPLEX/DUPLEX/TRIPLEX	Triplex (Playback/Recording/Ethernet)		
ZOOM	Available		
PIP	Available		
MOTION DETECT	Area Division: 16x12		
RECORDING MODE	Time, Motion, Schedule, Alarm, Emergency		
SEARCH MODE	Percentage Search, Date/Time Search, Event Search		
PASSWORD PROTECTION	Admin, Manager, User1-8 Allowed to access the system		
ALARM INPUT	8 Alarm (NO/NC)		
RELAY OUTPUT	1 (NO/NC)		
BACKUP	Download via IP Network, VCR, CD-RW, or DVD-RW back-up (option)		
IR REMOTE CONTROLLER	Built-in		
NETWORK (TCP/IP)	Remote Software (Remote live view, playback, and save as AVI), IE (Remote live view, backup to AVI), Two users access is available, transmission speed adjustable		
CMS	Available		
FIRMWARE UPGRADE	USB port for firmware upgrade		
OPERATION TEMPERATURE	41-104 F degrees		
OPERATION HUMIDITY	Less than 90%		
DIMENSION	430 x 400 x 92 mm (WxDxH)		
WEIGHT	Approx. 7.5kgs (w/o HDD)		
POWER SUPPLY	DC Adapter (12V DC 8A above)		